Business *Color Monitor*

15" (14.0" Viewable)

Up to 1280 x 1024 Resolution

.25mm Aperature Grill Dot Pitch

Trinitron® technology at an economical price. Designed with both PC and Mac® users in mind. User-friendly icon based onscreen controls. Resolutions of up to 1280 x 1024. Ideal for both office and home use.

15"
S - 1

DESIGNED *for*
PC&MAC

radius S1

miro displays, inc.
888.647.6462

www.mirodisplays.com

radius

S-1 BUSINESS COLOR MONITOR

SPECIFICATIONS

CRT	15¨ (14.0¨ viewable) Sony Trinitron®
Dot Pitch	.25 Aperture Grille
Scanning Frequency	Horizontal: 30kHz-70kHz Vertical: 50 Hz-140Hz
Max Resolution	1280 x 1024
Input Sync	Separate and composite TTL level
Signal Connector	HDB15 (PC) DB15M-HDB15F Adapter (Mac)
Power Supply	100-240 Vac @ 50/60Hz Nutek & EPA Energy Star compliant VESA DPMS compatible
Power Consumption	On Mode: 90W Standby: 15W Suspend: <15W Off Mode: <8W
Environmental Range (Operating)	32 to 104 deg. F (0 to 40 deg. C) 10%-80% humidity (noncondensing)
Pixel Rate/Bandwidth	108MHz
Dimensions (WxDxH)	14.4¨ x 15.8¨ x 14.5¨ 366mm x 402mm x 368mm
Weight	Net: 30.1 lbs. (13.7 kg) Gross: 35.0 lbs. (15.9 kg)

FEATURES

- Multi-scanning between 30kHz and 70kHz
- 15¨ (14.0¨ viewable) Sony Trinitron® tube
- Enhanced Brightness/Contrast, Moiré & Doming
- 0.25 Aperture Grille dot pitch
- Preset timing for PC and Mac
- Automatic Display Setup (in Preset Mode)
- Overscan capability for increased viewable area
- Compatible w/standard IBM VGA, extended VGA, superVGA, IBM XGA, SBA/2 & VESA ergonomic standards
- Windows 95 & 98 Plug & Play (VESA DDC1/2B, DDC2B+, DDC/CI)
- Compatible w/Apple Centris, Quadra & Power Mac
- Universal Power Supply
- Tilt-and-swivel base
- NUTEK and EPA Energy Star compliant power saving
- VESA Display Power Management Signaling (DPMS) compatible

USER CONTROLS

- Contrast
- Brightness
- H. Position
- H. Size
- V. Position
- V. Size
- Side-Pincushion
- Pin Balance
- Trapezoid
- Parallelogram
- Corner Pin
- Rotation
- Color Control (3 Preset, 1 User)
- R-Gain, G-Gain, B-Gain
- OSD Position
- Degauss
- Factory Preset Recall

REGULATORY APPROVALS

UL, CSA, CE, FCC-B, DHHS, TCO '95, NUTEK, EPA Energy Star, VESA DPMS, SEMKO

RESOLUTION

Mode	Screen Refresh Rate
640 x 480	up to 100Hz
800 x 600	up to 100Hz
1024 x 768	up to 85Hz
1152 x 864	up to 75Hz
1280 x 1024	up to 60Hz

DESIGNED *for* PC&MAC

miro displays, inc. • 1981 Landings Drive • Moutain View • CA 94043
888 • 647 • 6462

www.mirodisplays.com

Radius is a registered trademark of miro displays, inc. All products and brand names are registered trademarks of their respective companies. Specifications subject to change without prior notice.